

WINDIMURRA VANADIUM

WINDIMURRA VANADIUM PROJECT

STRUCTURAL DESIGN CRITERIA

PROJECT DOCUMENT NO.: 6033-G-00-S-002

В	15/01/08	Issued for Approval	ZP	RLD	LDW
А	24/11/06	Issued for Internal Checking	ZP RLD LDW		
NO	DATE REVISION DESCRIPTION		BY	CHK	APP





CONTENTS

1.0	GENERAL	1
1.1	Scope	1
1.2	Reference Documents	1
1.3	Precedence of Documents	1
2.0	SPECIFIC LOADING REQUIREMENTS	2
2.1	General AS1170	2
2.2	Dead Loads AS1170.1	2
2.3	Live Loads AS1170.1	2
2.4	Wind Loads AS1170.2	2
2.5	Earthquake Loads AS1170.4	3
2.6	References	3
3.0	STEELWORK DESIGN	4
3.1	General	4
3.2	Steel Grades	4
3.3	Corrosion Allowance	4
3.4	Other	4
3.5	References	4

06033BS002B - 1 -



1.0 GENERAL

1.1 Scope

This document sets out the structural design criteria for the Windimurra Vanadium Project.

1.2 Reference Documents

This design criteria shall be read in conjunction with the Structural Basis of Design document 6033-G-00-S-001.

1.3 Precedence of Documents

Specific loading requirements and design data and requirements from Proteus Structural Design Criteria shall override data from Proteus Basis of Design.

06033BS002B - 1 -



2.0 SPECIFIC LOADING REQUIREMENTS

2.1 General AS1170

Importance level
2 (Normal structures)

• Design working life 25 years

Geographical location
28deg 17m S; 118deg 32m E

2.2 Dead Loads AS1170.1

• Equipment self weight (certified vendor data)

Materials (specified by client)

Other

2.3 Live Loads AS1170.1

Equipment maintenance platform 5 kPa

Stairways and landings
4.0 kPa

Access and conveyor walkways
2.5 kPa

Electrical switchgear areas
10 kPa or 12 kN minimum

• Control rooms 5.0 kPa

• Storage areas 2.4 kPa/m of height (min 7.5 kPa)

Cable trays
1.0 kN/m

• Other

2.4 Wind Loads AS1170.2

• Wind region A4 (Figure 3.1)

• Annual probability of exceedance 250 years (Table F2)

• Terrain category TC 2 (Cl.4.2)

Wind direction multiplier
Md=1.0 (Cl.3.3)

• Shielding multiplier Ms=1.0 (Cl.4.3)

Topographic multiplier Mt=1.0 (Cl.4.4)

Other

06033BS002B - 2 -



2.5	Earthquake Loads		AS1170.4		
	•	Importance level	Normal (Table F1)		
	•	Annual probability of exceedance	1/50 years (Proteus scope only)		
	•	Acceleration coefficient	0.06		
	•	Site factor	S=0.67 (Table 2.4) footings on rock S=1.00 (Table 2.4) footings on fill		
	•	Earthquake design category	A (Table 2.6)		
	•	Structural response factor	As described in Table 6.2.6 (a) or Table 6.2.6 (b)		
	•	Other			
2.6	References				
	Windimurra Vanadium Project Geotechnical Investigation by Soil & Rock Engineering Pty Ltd (Ref. gb2718_2rep.doc, 9-Sep-98				
2					
	3				
	4				
	5				
	6				
	7				
	8				
	9				
	10				

Table 2.6 to be populated with data and vendor information as they become available.

06033BS002B - 3 -



3.0 STEELWORK DESIGN

3.1 General

• Design Code AS4100

3.2 Steel Grades

• Steel Plate 300 MPa

Hot Rolled Sections 300 MPa

• Structural Hollow Sections 350 MPa

Bolts, Nuts and Washers
8.8 grade UON

3.3 Corrosion Allowance

Corrosion Allowance
Not required for structural steel

Minimum wall thickness 5 mm

Protection System Refer Standard Specification for Painting and Protective Coatings

6033-S-00-G-009

3.4 Other

3.5 References

1

2

3

4

5

6

7

8

9

10

06033BS002B - 4 -